

DIN 2569

Presion nominal 100 / Rated pressure 100 / Nenndruck 100

Diámetro Nominal Rated Diameter Nennweite	d1	Brida / Flange / Flansch				Cuello / Neck / Ansatz				Resalto / Raised face / Dichtleiste		Tornillos / Screws / Schrauben			Peso de una brida / Weight of a flange / Gewicht eines Flansches (7,85 Kg/dm ³)	
		Rosca / Thread / Whitworth- Rohrgewinde DIN 2999	D	b	k	h1	d3	d5	p	r	d4	f	Numero / Number / Anzahl	Rosca / Thread / Gewinde	d2	Kg
10	17,2	R 3/8	100	20	70	28	40	18	4	2	50	2	4	M 12	14	1,08
15	21,3	R 1/2	105	20	75	28	43	22	6	2	55	2	4	M 12	14	1,19
20	26,9	R 3/4	130	22	90	30	52	28	7	2	68	2	4	M 16	18	2
25	33,7	R 1	140	24	100	32	60	35	7	3	78	2	4	M 16	18	2,54
32	42,4	R 1 1/4	155	24	110	32	68	43	7	3	85	2	4	M20	22	2,99
40	48,3	R 1 1/2	170	26	125	34	80	49	7	3	98	3	4	M20	22	3,87
50	60,3	R 2	195	28	145	36	95	61	7	3	115	3	4	M24	26	5,42
65	76,1	R 2 1/2	220	30	170	40	118	77	7	3	140	3	8	M24	26	7,11
80	88,9	R 3	230	32	180	44	130	90	7	3	150	3	8	M24	26	8,21
100	114	R 4	265	36	210	52	158	116	7	3	175	3	8	M27	30	12,1
125	140	R 5	315	40	250	56	188	141	7	3	210	3	8	M30	33	18,6
150	165	R 6	355	44	290	60	225	167	7	3	250	3	12	M30	33	25,1

