

DIN 2627

Bridas con cuello para soldar
Presion nominal 400

Welding neck flanges
Rated pressure 400

Vorschweißflansche
Nenndruck 400

Medidas en milímetros
Dimensions in mm
Maße in mm

Tubo / Pipe / Rohr - Anschlußmaße		Brida / Flange / Flansch				Cuello / Neck / Ansatz				Resalto / Raised face / Dichtleiste		Tornillos / Screws / Schrauben			Peso de una brida / Weight of a flange / Gewicht eines Flansches (7,85 Kg/dm ³)
Diámetro Nominal Rated Diameter Nennweite	d1	D	b	k	h1	d3	s	r	h2	d4	f	Numero / Number / Anzahl	Rosca / Thread / Gewinde	d2	Kg
	ISO Serie 1 Reihe 1														
10	17,2	125	28	85	65	48	3,6	4	8	40	2	4	M 16	18	2,52
15	26,9	145	30	100	68	56	5	4	8	45	2	4	M20	22	3,59
25	42,4	180	38	130	90	82	7,1	4	10	68	2	4	M24	26	7,43
40	60,3	220	48	165	110	106	10	6	12	88	3	4	M27	30	14
50	76,1	235	52	180	120	120	12,5	6	15	102	3	8	M27	30	16,7
65	101,6	290	64	225	135	158	16	6	18	122	3	8	M30	33	31,6
80	114,3	305	68	240	150	174	17,5	8	20	138	3	8	M30	33	38,4
100	139,7	370	80	295	175	216	22,2	8	25	162	3	8	M36	39	67,3
125	193,7	415	92	340	200	258	30	8	30	188	3	12	M36	39	96
150	219,7	475	105	390	225	302	35	10	35	218	3	12	M39	42	146
200	273	585	130	490	280	388	40	10	40	285	3	16	M45	48	296

