



DIN 2633

Bridas con cuello para soldar
Presion nominal 16

Welding neck flanges
Rated pressure 16

Vorschweißflansche
Nennndruck 16

Med das en milímetros
Dimens ons in mm
Maße in mm

Tubo / Pipe / Rohr - Anschlußmaße			Brida / Flange / Flansch				Cuello / Neck / Ansatz				Resalto / Raised face / Dichtleiste		Tornillos / Screws / Schrauben			Peso de una brida / Weight of a flange / Gewicht eines Flansches (7,85 Kg/dm ³)
Diámetro Nominal Rated Diameter Nennweite	d1		D	b	k	h1	d3	s	r	h2	d4	f	Numero / Number / Anzahl	Rosca / Thread / Gewinde	d2	
	ISO Serie 1 Reihe 1	DIN Serie 2 Reihe 2														
10	-	14	90	14	60	35	25	1,8	4	6	40	2	4	M 12	14	0,58
	17,2	-														
15	-	20	95	14	65	35	30	2	4	6	45	2	4	M 12	14	0,648
	21,3	-														
20	-	25	105	16	75	38	38	2,3	4	6	58	2	4	M 12	14	0,952
	26,9	-														
25	-	30	115	16	85	38	42	2,6	4	6	68	2	4	M 12	14	1,14
	33,7	-														
32	-	38	140	16	100	40	52	2,6	6	6	78	2	4	M 16	18	1,69
	42,4	-														
40	-	44,5	150	16	110	42	60	2,6	6	7	88	3	4	M 16	18	1,86
	48,3	-														
50	-	57	165	18	125	45	72	2,9	6	8	102	3	4	M 16	18	2,53
	60,3	-														
65	76,1	-	185	18	145	45	90	2,9	6	10	122	3	4	M 16	18	3,06
80	88,9	-	200	20	160	50	105	3,2	8	10	138	3	8	M 16	18	3,7
100	-	108	220	20	180	52	125	3,6	8	12	158	3	8	M 16	18	4,62
	114,3	-														
125	-	133	250	22	210	55	150	4	8	12	188	3	8	M 16	18	6,3
	139,7	-														
150	-	159	285	22	240	55	175	4,5	10	12	212	3	8	M20	22	7,75
	168,3	-														
(175)	193,7	-	315	24	270	60	210	5,4	10	12	242	3	8	M20	22	9,85
200	219,1	-	340	24	295	62	235	5,9	10	16	268	3	12	M20	22	11
250	-	267	405	26	355	70	285	6,3	12	16	320	3	12	M24	26	15,6
	273	-														
300	323,9	-	460	28	410	78	344	7,1	12	16	378	4	12	M24	26	22
350	355,6	-	520	30	470	82	390	8	12	16	438	4	16	M24	26	31,2
	-	368														28,8
400	406,4	-	580	32	525	85	445	8	12	16	490	4	16	M27	30	39,3
	-	419														36,3
(450)	457	-	640	34	585	85	490	8	12	16	550	4	20	M27	30	44,3
500	508	-	715	34	650	90	548	8	12	16	610	4	20	M30	33	61
600	610	-	840	36	770	95	652	8,8	12	18	725	5	20	M33	36	75,4
700	711	-	910	36	840	100	755	8,8	12	18	795	5	24	M33	36	77
800	813	-	1025	38	950	105	855	10	12	20	900	5	24	M36	39	101
900	914	-	1125	40	1050	110	955	10	12	20	1000	5	28	M36	39	122
1000	1016	-	1255	42	1170	120	1058	10	16	22	1115	5	28	M 39	42	162
1200	1220	-	1485	48	1390	130	1262	13	16	30	1330	5	32	M45	48	243
1400	1420	-	1685	52	1590	145	1465	14	16	30	1530	5	36	M45	48	323
1600	1620	-	1930	58	1820	160	1668	16	16	35	1750	5	40	M52	56	479
1800	1820	-	2130	62	2020	170	1870	18	16	35	1950	5	44	M52	56	599
2000	2020	-	2345	66	2230	180	2072	20	16	40	2150	5	48	M56	62	719