

# DIN 28115

Medidas en milímetros  
Dimens ons in mm  
Maße in mm

**Bridas con cuello largo para soldar**  
**Presion nominal 25**

**Long welding neck flanges**  
**Rated pressure 25**

**Flanschutzen**  
**Nenndruck 25**

Diámetro Nominal Rated Diameter Nennweite	Presión Nominal / Nominal pressure / Nenndruck			Presión de Servicio a 200ª C / Service Pressure to 200ª C / Betriebsdruck bis 200ª C	Tubo / Pipe / Rohr		Brida / Flange / Flansch				Cuello / Neck / Ansatz		Resalto / Raised face / Dichtleiste		Tornillos / Screws / Schrauben			Peso de una brida / Weight of a flange / Gewicht eines Flansches (7,85 Kg/dm³) Kg	
	Kg/cm²	Kg/cm²	Kg/cm²		a	s	D	j	b	h	m	r	g	f	k	Numero / Number / Anzahl	l		Rosca / Thread / Gewinde
25	16	25	40	32	38	7	115	24	18	120	50	8	68	2	85	4	14	M 12(1/2")	1,9
32	16	25	40	32	51	8	140	35	18	120	62	8	78	2	100	4	18	M 16(5/8")	3
40	16	25	40	32	57	8	150	41	18	120	70	8	88	3	110	4	18	M 16(5/8")	3,2
50	16	25	40	32	70	8	165	54	20	120	85	8	102	3	125	4	18	M 16(5/8")	4,5
65	16	.	.	13	89	8	185	73	22	170	104	8	122	3	145	4	18	M 16(5/8")	7,5
	.	25	40	32	89	8	185	73	22	170	104	8	122	3	145	8	18	M 16(5/8")	7,3
80	16	.	.	13	102	8	200	86	24	170	118	8	138	3	160	8	18	M 16(5/8")	8,4
	.	25	40	32	102	8	200	86	24	170	118	8	138	3	160	8	18	M 16(5/8")	8,4
100	16	.	.	13	121	10	220	101	24	170	138	8	158	3	180	8	18	M 16(5/8")	9,8
125	16	.	.	13	146	10	250	126	26	170	164	10	188	3	210	8	18	M 16(5/8")	12,6
150	16	.	.	13	171	10	285	151	28	170	188	10	212	3	240	8	23	M20 (3/4")	15,8
200	16	.	.	13	224	10	340	204	34	170	246	10	268	3	295	12	23	M20 (3/4")	24,2

